



### ■ Main Features


- )] High efficiency and extremely compact size
- )] Only 35mm width aluminum enclosure
- )] Active PFC
- )] Overload 125%
- )] High operating temperature with no derating

## TECHNICAL DATA

Model type	MEPS150-24	
<b>OUTPUT DATA</b>		
Rated voltage	24Vdc	
Adj. output voltage range	24Vdc Fixed	
Continuous current	6.0A	
Overload limit	7.5A	
Load regulation	≤ 1%	
Ripple & Noise <sup>1</sup>	≤ 50mVpp	
Hold up time Vin = 120Vac	≥ 20ms	
Vin = 240Vac	≥ 30ms	
Protections	<ul style="list-style-type: none"> <li>▪ Overload, short circuit: with Constant current</li> <li>▪ Thermal protection</li> <li>▪ Input undervoltage lockout</li> <li>▪ Output overvoltage</li> </ul>	
Output overvoltage protection	≥ 33Vdc	
Status Signals	<ul style="list-style-type: none"> <li>▪ <b>DC OK</b> - green LED</li> <li>▪ <b>OVERLOAD</b> - red LED</li> </ul>	
Parallel connection	Possible for power or redundancy (with external ORing module)	
<b>INPUT DATA</b>		
Input AC rated voltage	Nominal: 120...240Vac	
Frequency	Range: 90...264Vac 47...63Hz	
Input DC rated voltage	110...345Vdc	
Input AC rated current Vin = 120Vac	1.5A	
Vin = 240Vac	0.8A	
Input DC rated current Vin = 110Vdc	1.5A	
Vin = 345Vdc	0.6A	
Power factor correction	Active / > 0.9	
Inrush peak current	≤ 30A	
Touch (leakage) current	≤ 0.5mA	
Internal protection fuse	Fuse 3.15AT (not user replaceable)	
Recommended external protection	Fuse 4AT or MCB 4A C curve It is strongly recommended to provide external surge arresters (SPD) according to local regulations.	
<b>GENERAL DATA</b>		
Efficiency	> 90.7%	
Dissipated power	< 15W	
Operating temperature <sup>2</sup>	- 35°C...+ 70°C	
Derating	- 4.5W/°C over 50°C	
Storage temperature	- 40°C...+ 80°C	
Humidity	5...95% r.H. non condensing	
Life time expectation	74'640h (8.5 years) at 25°C ambient full load	
Overvoltage category	▪ EN50178	III
Pollution degree	▪ IEC60664-1	2
Protection Class	▪ CLASS	I
Input / output isolation	4.2kVdc	
Input / ground isolation	2.2kVdc	
Output / ground isolation	0.75kVdc	
Safety Standards	<ul style="list-style-type: none"> <li>▪ UL508 (pending)</li> <li>▪ EN60950 (reference)</li> <li>▪ EN50178 (reference)</li> </ul>	
EMC Emission	<ul style="list-style-type: none"> <li>▪ EN55011 (CISPR11) Class B</li> <li>▪ EN55022 (CISPR22) Class B</li> <li>▪ EN61000-3-2 Class A</li> </ul>	
EMC Immunity	<ul style="list-style-type: none"> <li>▪ EN61000-4-2 Level 3</li> <li>▪ EN61000-4-3 Level 3</li> <li>▪ EN61000-4-4 Level 4</li> <li>▪ EN61000-4-5 Level 4</li> <li>▪ EN61000-4-11 Level 2</li> </ul>	
Protection degree	▪ EN60529	IP20
Vibration sinusoidal	▪ IEC 60068-2-6	(5-17.8Hz: ±1.6mm; 17.8-500Hz: 2g 2hours / axis (X,Y,Z))
Shock	▪ IEC 60068-2-27	(30g 6ms, 20g 11ms; 3 bumps / direction, 18 bumps total)

Connection terminals	2.5mm <sup>2</sup> , screw type pluggable (24...12AWG)
Case material	Aluminum
Weight	0.45kg
Size (W x H x D)	35.0 x 103.0 x 104.0mm
1) Ripple and Noise are measured with 20MHz bandwidth, probe terminated with a 0.1µF MKP parallel capacitor. 2) Start-up type tested: - 20°C, possible at nominal voltage with load deration.	
<b>Notes:</b> - Technical parameters are typical, measured in laboratory environment at 25°C and 240Vac / 50Hz, at nominal values, after minimum 5 minutes of operation. - Power rating, losses, efficiency, ripple, thermal behaviour and start-up may change outside of the nominal rated input range. Contact factory for details. - Data may change without prior notice in order to improve the product.	

**DIMENSIONS**



**CONNECTION**



**Input Connection:**

- Single phase:
- L = Line
  - N = Neutral
  - | = Earth ground
- DC:
- L = + Positive DC
  - N = - Negative DC
  - | = Earth ground

**Output Connection:**

- += Positive DC
- -= Negative DC